

## MULTIWAX® ML-445 Microcrystalline Wax

Page 1 of 6

---

Date of issue: 9/17/2012 Version: 3

Sonneborn, LLC urges the recipient of this Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety you should (1) notify your employees, agents and contractors of the information of this sheet, (2) furnish a copy to each of your customers for the product and (3) request your customers to inform their employees and customers as well.

---

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

---

**Identification of the substance or preparation**

Microcrystalline Wax

**Use of substance/preparation:**

Microcrystalline waxes typically used as a blending base in a variety of applications including cosmetic, pharmaceutical, food and general industrial.

**Company identification**

Sonneborn, LLC  
600 Parsippany Road, Suite 100  
Parsippany, NJ 07054 USA

**Emergency telephone number**

Chemtrec (24hrs): 800-424-9300  
Sonneborn: 724-756-2210

---

### 2. HAZARDS IDENTIFICATION

---

GHS Classification :Not classified as dangerous under EC/GHS-criteria

Human Health Hazards :None

Physico-chemical and environmental hazards and effects: None

**HMIS RATING USA**

Health: 0	Flammability: 1	Reactivity: 0	PPI: -
-----------	-----------------	---------------	--------

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

INGREDIENT	% BY WEIGHT	CAS #	HAZARD	DANGER SYMBOL(S)
Microcrystalline Wax	100	63231-60-7		

---

### 4. FIRST AID MEASURES

---

**Swallowing**

WHEN MOLTEN ONLY (molten product can cause thermal burns). Obtain medical attention immediately. This is not a toxic substance.

## MULTIWAX® ML-445 Microcrystalline Wax

### Inhalation

No emergency care anticipated. WHEN MOLTEN ONLY (molten product can cause thermal burns). Obtain medical attention immediately. Exposed persons should be kept under medical observation for at least 48 hours because delayed effects may occur.

### Skin

WHEN MOLTEN ONLY (molten product can cause thermal burns) – In serious cases, use emergency shower immediately. Immediately flush skin thoroughly with cold water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention.

### Eye contact

WHEN MOLTEN ONLY (molten product can cause thermal burns) – Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention.

## 5. FIRE-FIGHTING MEASURES

**Flash Point:** >93.4°C (200°F) PMCC ASTM D93

### NFPA CLASSIFICATION USA

Health: 0      Flammability: 1      Reactivity: 0      Special provisions: -

### Extinguishing media

Suitable:      Treat as an oil fire:  
- dry chemical  
- carbon dioxide (in case of small fires)  
- water fog  
- foam

Unsuitable:      Do not use water jet. Oil will float on water and can spread any fire.

### Special fire fighting procedures

Do not direct a solid stream of water or foam into burning material; this may cause spattering and spread the fire. If a rail or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

### Special protective equipment for firefighters

Self-contained breathing apparatus.

### Unusual fire and explosion hazards

Following products may be produced during a fire: Oxides of carbon.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions

Wear suitable protective equipment.

### MULTIWAX® ML-445 Microcrystalline Wax

Page 3 of 6

---

#### Environmental precautions

Avoid runoff to sewers or waterways. Dike area of spill to prevent spreading and pump liquid to salvage tank. Waste: avoid washing into watercourses. Use methods consistent with local regulations or incinerate.

#### Methods for cleaning up

Dike to contain spill. Absorb on inert material such as sand, earth, vermiculite. After cooling, scrape and/or shovel material. Stop the leak if it can be done without risk. Floor may be slippery; use care to avoid falling.

---

## 7. HANDLING AND STORAGE

#### HANDLING

Do not handle at temperatures  $>+40^{\circ}\text{C}$ , unless wearing appropriate protective equipment.

#### Ventilation

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

#### STORAGE

##### Storage requirements

Keep away from heat, sparks and flame. Do not store at temperatures:  $>+40^{\circ}\text{C}$  without proper safety review of storage equipment. Store protected from light.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### EXPOSURE LIMIT VALUES

No exposure limits have been established.

#### OCCUPATIONAL EXPOSURE CONTROLS

##### Respiratory protection

None expected to be needed.

##### Hand protection/protective gloves

Wear oil resistant gloves. WHEN MOLTEN ONLY: wear gloves impervious to this material and able to resist and protect employees from the elevated temperature.

##### Eye protection

WHEN MOLTEN ONLY: Face shield or chemical splash goggles in case of splashing.

##### Skin protection

WHEN MOLTEN ONLY: Wear protective clothing, such as long sleeves to minimize skin contact.

##### Environmental Exposure Controls:

None expected to be needed.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Appearance

## MULTIWAX® ML-445 Microcrystalline Wax

Page 4 of 6

---

Physical State:	Solid
Color:	White to yellow
Odor:	None or Mild Petroleum
Odor Threshold:	N/A

### Important health, safety and environmental information

Flash Point:	>93.4°C (200°F) Method: PMCC, ASTM D93
Upper explosion limits:	Not determined
Lower explosion limits:	Not determined
Vapor Pressure:	<0.1 kPa at 20°C
Density:	>0.80 g/cm <sup>3</sup> at 100°C
Bulk Density:	Not available
Solubility in Water:	Insoluble
Solubility in organic solvents:	Soluble
Kinematic viscosity:	13 – 18 mm <sup>2</sup> /s at 100°C
Boiling Point:	> 230°C
PH:	N/A
Specific gravity (H <sub>2</sub> O=1)	<1
Partitioning coefficient	log POW: >6 This product is soluble in oil.
Vapor Density:	N/A
Percent volatiles	Nil
Autoignition Temperature:	No Data
Melting Point:	54 - 102°C unless specified below

---

## 10. STABILITY AND REACTIVITY

---

**Stability:** Stable

**Conditions/Materials to avoid:** Extreme temperature and direct sunlight/ultraviolet light and strong oxidizing agents.

### Hazardous combustion products

Burning can produce the following combustion products: Oxides of carbon and Soot

**Hazardous polymerization:** Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

### GENERAL

No evidence of harmful effects from available information.

---

## 12. ECOLOGICAL INFORMATION

---

This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant.

## MULTIWAX® ML-445 Microcrystalline Wax

---

### 13. DISPOSAL CONSIDERATIONS

---

Dispose of in accordance with appropriate Federal, State and local regulations or incinerate.

---

### 14. TRANSPORT INFORMATION

---

#### ADR/RID

(when transported at <100°C ) This product is not regulated by ADR.

When transported above >100°C – UN3257 ELEVATED TEMPERAURE LIQUIDS, N.O.S. (9), III, **Class:** 9 (M9), **UN No.:** 3257, **Packaging Group:** III, **Hazard No.:** 99, **Label:** 9, **Technical Description:** Microcrystalline Wax

Freight Description Road: 65 Petroleum Oil, N.O.I.B.N.

#### IMDG/ICAO

This product is not regulated by IMDG/ICAO.

FORBIDDEN BY AIR @ >= 100°C

#### TDG-CANADA

This product is not regulated by TDG.

---

### 15. REGULATORY INFORMATION

---

#### EC/GHS classification

According to EC/GHS regulations this product is not classified or labeled

#### New Jersey Worker and Community Right-To-Know Act (Labeling Requirements)

Chemical name	CAS#	New Jersey TS Number
Microcrystalline Wax	63231-60-7	

**EPA Hazard Categories (SARA 311, 312):** None

**WHMIS Classification:** This product is not a WHMIS controlled product.

#### Chemical Inventory

<u>Canada:</u>	The ingredients of this product are on the DSL.
<u>Europe:</u>	The ingredients of this product are on the EINECS inventory.
<u>United States:</u>	The ingredients of this product are on the TSCA inventory.
<u>Australia:</u>	The ingredients of this product are on the AICS inventory.
<u>Japan:</u>	The ingredients of this product are on the ENCS inventory.

### MULTIWAX® ML-445 Microcrystalline Wax

Page 6 of 6

---

#### 16. OTHER INFORMATION

---

##### **Recommended uses and restrictions**

Please consult the product and/or application information bulletins for this product.

##### **Further information, Europe**

Where appropriate, use CE approved personal protection equipment.

This Safety Data Sheet conforms to EC Directive 1907/2006 and amendments.

The opinions expressed herein are those of qualified experts within Sonneborn, LLC. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn, LLC it is the user's obligation to determine the conditions of safe use of the products.