

WITCOGEL[®] II Cable Filler

Page 1 of 6

Revision Date: 5/29/2015 Version: 5 Issue Date: 6/11/2015

Sonneborn, LLC urges the recipient of this Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety you should (1) notify your employees, agents and contractors of the information of this sheet, (2) furnish a copy to each of your customers for the product and (3) request your customers to inform their employees and customers as well.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Cable Filler

Use of substance/preparation:

Cable Filler is a blend of non-hazardous hydrocarbons. It is not expected to present any unusual hazards in proper use.

Company identification

Sonneborn, LLC
600 Parsippany Road, Suite 100
Parsippany, NJ 07054 USA

Emergency telephone number

Chemtrec (24hrs): 800-424-9300
Sonneborn: 724-756-2210

2. HAZARDS IDENTIFICATION

GHS Classification :Not classified as dangerous under EC/GHS-criteria

Human Health Hazards :None

Physico-chemical and environmental hazards and effects: None

HMIS RATING USA

Health: 0	Flammability: 1	Reactivity: 0	PPI: -
-----------	-----------------	---------------	--------

3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	% BY WEIGHT	CAS #	HAZARD	DANGER SYMBOL(S)
------------	-------------	-------	--------	------------------

Contains no Hazardous Substances

4. FIRST AID MEASURES

Swallowing

WHEN MOLTEN ONLY (molten product can cause thermal burns). Obtain medical attention immediately. This is not a toxic substance.

WITCOGEL® II Cable Filler

Inhalation

No emergency care anticipated. WHEN MOLTEN ONLY (molten product can cause thermal burns). Obtain medical attention immediately.

Skin

WHEN MOLTEN ONLY (molten product can cause thermal burns) – In serious cases, use emergency shower immediately. Immediately flush skin thoroughly with water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention.

Eye contact

WHEN MOLTEN ONLY (molten product can cause thermal burns) – Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash Point: >93.4°C (200°F) PMCC, ASTM D93
--

NFPA CLASSIFICATION USA

Health: 0	Flammability: 1	Reactivity: 0	Special provisions: -
-----------	-----------------	---------------	-----------------------

Extinguishing media

Suitable: Treat as an oil fire:
- dry chemical
- carbon dioxide (in case of small fires)
- water fog
- foam

Unsuitable: Do not use water jet. Oil will float on water and can spread any fire.

Special fire fighting procedures

Do not direct a solid stream of water or foam into burning material; this may cause spattering and spread the fire. If a rail or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

Special protective equipment for firefighters

Self-contained breathing apparatus.

Unusual fire and explosion hazards

Following products may be produced during a fire: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear suitable protective equipment.

Environmental precautions

WITCOGEL[®] II Cable Filler

Page 3 of 6

Avoid runoff to sewers or waterways. Dike area of spill to prevent spreading and pump liquid to salvage tank. Waste: avoid washing into watercourses. Use methods consistent with local regulations or incinerate.

Methods for cleaning up

Dike to contain spill. Absorb on inert material such as sand, earth, vermiculite. After cooling, scrape and/or shovel material. Stop the leak if it can be done without risk. Floor may be slippery; use care to avoid falling.

7. HANDLING AND STORAGE

HANDLING

Do not handle at temperatures $>+40^{\circ}\text{C}$, unless wearing appropriate protective equipment.

Ventilation

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

STORAGE

Storage requirements

Keep away from heat, sparks and flame. Do not store at temperatures: $>+40^{\circ}\text{C}$ without proper safety review of storage equipment. Store protected from light.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

No exposure limits have been established.

OCCUPATIONAL EXPOSURE CONTROLS

Respiratory protection

None expected to be needed.

Hand protection/protective gloves

Wear oil resistant gloves. WHEN MOLTEN ONLY: wear gloves impervious to this material.

Eye protection

WHEN MOLTEN ONLY: Face shield or chemical splash goggles in case of splashing.

Skin protection

WHEN MOLTEN ONLY: Wear protective clothing, such as long sleeves to minimize skin contact.

Environmental Exposure Controls:

None expected to be needed.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State: Solid

WITCOGEL[®] II Cable Filler

Color:	White to yellow
Odor:	Mild Petroleum
Odor Threshold:	N/A

Important health, safety and environmental information

Flammability	No Data
Evaporation Rate	No Data
Decomposition Temperature	No Data
Flash Point:	>93.4°C (200°F) Method: PMCC, ASTM D93
Upper explosion limits:	Not determined
Lower explosion limits:	Not determined
Vapor Pressure:	No Data
Density:	0.75 – 0.87 g/cm ³ at 100°C
Bulk Density:	Not available
Solubility in Water:	Insoluble
Solubility in organic solvents:	Soluble
Kinematic viscosity:	5 – 30 mm ² /s at 100°C
Boiling Point:	> 230°C
PH:	N/A
Specific gravity (H ₂ O=1)	<1
Partitioning coefficient	log POW: >6 This product is soluble in oil.
Vapor Density:	N/A
Percent volatiles	Nil
Autoignition Temperature:	No Data
Melting Point:	85 - 125°C

10. STABILITY AND REACTIVITY

Stability: Stable

Conditions/Materials to avoid: Extreme temperature and direct sunlight/ultraviolet light and strong oxidizing agents.

Hazardous combustion products

Burning can produce the following combustion products: Oxides of carbon and Soot

Hazardous polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

GENERAL

No evidence of harmful effects from available information.

WITCOGEL[®] II Cable Filler

12. ECOLOGICAL INFORMATION

This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with appropriate Federal, State and local regulations or incinerate.

14. TRANSPORT INFORMATION

ADR/RID

(when transported at <100°C) This product is not regulated by ADR.

When transported above >100°C – UN3257 ELEVATED TEMPERAURE LIQUIDS, N.O.S. (9), III, **Class:** 9 (M9), **UN No.:** 3257, **Packaging Group:** III, **Hazard No.:** 99, **Label:** 9, **Technical Description:** Petroleum Jelly

Freight Description Road: 65 Petroleum Oil, N.O.I.B.N.

IMDG/ICAO

This product is not regulated by IMDG/ICAO.

TDG-CANADA

This product is not regulated by TDG.

15. REGULATORY INFORMATION

EC/GHS classification

According to EC/GHS regulations this product is not classified or labeled

New Jersey Worker and Community Right-To-Know Act (Labeling Requirements)

Chemical name	CAS#	New Jersey TS Number
---------------	------	----------------------

EPA Hazard Categories (SARA 311, 312): None

WHMIS Classification: This product is not a WHMIS controlled product.

Chemical Inventory

<u>Canada:</u>	The ingredients of this product are on the DSL.
<u>Europe:</u>	The ingredients of this product are on the EINECS inventory.
<u>United States:</u>	The ingredients of this product are on the TSCA inventory.
<u>Australia:</u>	The ingredients of this product are on the AICS inventory.
<u>Japan:</u>	The ingredients of this product are on the ENCS inventory.

WITCOGEL[®] II Cable Filler

16. OTHER INFORMATION

Recommended uses and restrictions

Please consult the product and/or application information bulletins for this product.

Further information, Europe

Where appropriate, use CE approved personal protection equipment.

This Safety Data Sheet conforms to EC Directive 1907/2006 and amendments.

The opinions expressed herein are those of qualified experts within Sonneborn, LLC. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn, LLC, it is the user's obligation to determine the conditions of safe use of the products.