

Specifications for 40 OIL

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Specific Gravity @ 25°C/25°C	ASTM D4052	0.810/0.830
Kin. Viscosity @ 40°C, mm ² /s	ASTM D445	3.9/5.0
Acidity	NF (current revision)	PASS
Readily Carbonizable Substances	NF (current revision)	PASS
Solid Paraffin	NF (current revision)	PASS
Limit Of Polycyclic Aromatic Hydrocarbons	NF (current revision)	PASS
Sulfur Compounds	NF (current revision)	PASS
Odor	LATM 092	NONE
Color, Saybolt	ASTM D156	30 Min.
Breakdown Time, Minutes	LATM 017	40 Min.
Cloud Point, °C	ASTM D2500	5 Max.
Pour Point, °C	ASTM D97	3 Max.
Flash Point, COC, °C	ASTM D92	120 Min.
Water, ppm	ASTM D6304	50 Max.
Appearance	LATM 127	BRIGHT & CLEAR
Residual Solvents, Reportable Quantity	USP 467	None
Infrared Absorption	USP 197F	PASS

This product meets FDA requirement as per 21 CFR 172.878 and 178.3620(A).

TYPICAL PROPERTIES FOR 40 OIL

<u>PROPERTIES</u>	<u>TEST METHOD</u>	<u>TYPICAL VALUE</u>
Refractive Index @ 25°C	ASTM D1218	1.450

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.