

Specifications for CABLE FILLER 7B

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
COLOR	ASTM D1500	2.5 Max.
SPECIFIC GRAVITY @ 266°F/60°F	ASTM D176	0.79/0.81
TOTAL ACID NUMBER	ASTM D974	0.06 Max.
MELTING POINT, °F	ASTM D127	205/215
FLASH POINT, °F	ASTM D92	440 Min.
VOLATILITY, %	ASTM D6	0.8 Max.
VISCOSITY @ 266°F, SUS	ASTM D445	60/100
DIELECTRIC CONSTANT @ 10 ⁶ Hz	ASTM D150	2.30 Max.
DISSIPATION FACTOR @ 10 ⁶ Hz	ASTM D150	0.0015 Max.
VOLUME RESISTIVITY, OHM-cm	ASTM D257	1X10 ¹² Min.
SLUMP/FLOW TEST, 2 hrs/190°F	LATM 040	PASS

TYPICAL PROPERTIES FOR CABLE FILLER 7B Grade

<u>PROPERTIES</u>	<u>TEST METHOD</u>	<u>TYPICAL VALUE</u>
CONSISTENCY	ASTM D937	50