

Specifications for  
**CARNATION® Trough Grease Regular**

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Pour Point, °F	ASTM D97	90/100
Lovibond Color, 2" CELL, Y	IP 17	1.0 Max.
Viscosity @ 130°F, SUS	ASTM D2161	65 Min.
Consistency	ASTM D937	200/225
Residual Solvents, Reportable Quantity	USP 467	NONE
Odor Rating, Panel Average	LATM 093	0.8 Max.

This product is a blend of White Petrolatum USP meeting requirements for USP (current revision) and FDA as per 21 CFR 172.880, Paraffin NF meeting FDA requirements as per 21 CFR 172.886 and Light Mineral Oil NF meeting FDA requirements as per 21 CFR 172.878.

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.