

## Specifications for D/F FLUID 21

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Specific Gravity @ 25°C/25°C	ASTM D4052	0.780/0.820
Kin. Viscosity @ 40°C, mm <sup>2</sup> /s	ASTM D445	2.0/5.0
Approved for use in Food	21CFR172.878	PASS
Color, Saybolt	ASTM D156	30 Min.
Flash Point, PMCC, °F	ASTM D93	200 Min.
Pour Point, °C	ASTM D97	-18 Max.
BTEX	EPA 8260B	None Detected

D/F Fluid 21 is a high boiling lubricating fraction that is purified by two-stage, High Pressure/High Temperature Catalytic Hydrogenation and vacuum fractionation. This purification process provides a liquid that complies with the requirements for direct food addition as per 21CFR172.878. The purification process along with a distillation range (as per ASTM D2887-GC Method) that is 75°C higher than o-xylene precludes the presence of BTEX compounds in D/F Fluid 21.

5189235

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.