

Specifications for PD-23

| <u>PROPERTIES GUARANTEED</u> | <u>TEST METHOD</u> | <u>LIMITS</u> |
|---|--------------------|---------------|
| Specific Gravity @ 60°F/60°F | ASTM D4052 | 0.795/0.810 |
| Kinematic Visc. @ 100°F, mm ² /s | ASTM D445 | 2.9 Max. |
| Saybolt Visc. @ 100°F, SUS | ASTM D2161 | 34.0/36.0 |
| UV Absorbance | 21CFR 178.3620(b) | PASS |
| Color, Saybolt | ASTM D156 | 30 Min. |
| Breakdown Time, Minutes | LATM 017 | 40 Min. |
| Flash Point, COC, °F | ASTM D92 | 225 Min. |
| Distillation, 5%, °C | ASTM D2887 | 215 Min. |
| Distillation, 95%, °C | ASTM D2887 | 305 Max. |

0414151004P

14132/14133

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.

Sonneborn, LLC
600 Parsippany Road
Suite 100
Parsippany, NJ 07054

Technical Service 877.541.7144
Customer Service 877.948.2688
Fax 724.756.9386
www.sonneborn.com