

Specification for
SONOLUBE® 168 Compressor Lubricant

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Specific Gravity @ 25°C	ASTM D4052	0.855/0.884
Viscosity @ 40 °C, cSt	ASTM D445	108/126
Neutralization No., mg KOH/g	ASTM D974	1.65/2.35
Flash Point, COC, °C	ASTM D92	218 Min.
Pour Point, °C	ASTM D97	-9 Max.
Appearance	VISUAL	PASS
Color	ASTM D1500	1.0 Max.
Water Content, ppm	ASTM D6304	75 Max.
Odor	SMELL	Slight Polybutene

This product is blended from FDA approved components meeting 21 CFR 178.3570 requirements.

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.