

Specifications for
VISCONORUST 2090 P-4

<u>PHYSICAL PROPERTIES</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Density (lbs/gal) @ 60°F (15.6°C)	ASTM D-1298	7.3-7.8
Specific gravity @ 60°F (15.6°C)	ASTM D-1298	0.88-0.94
Congealing Point, °F (°C)	ASTM D938	135 (57) min
Flash Point, °F (°C)	ASTM D92	420 (215) min
Viscosity, SUS @ 210°F	ASTM D-88	130 min
Consistency (Cone Penetration) @ 77 °F	ASTM D937	170-200
Total Base No. (Modified)	ASTM D-974	35 min
Water Content (wt. %)	ASTM D-95	0.4 max

CHEMICAL PROPERTIES (Note: ASME Boiler & Pressure Vessel Code Sec. III, Div. 2, Table CC-2442-1)

Water Soluble Chlorides	ASTM D-512	2 ppm max
Water Soluble Nitrates	ASTM D-3867 (See Note 1)	4 ppm max
Water Soluble Sulfides	APHA 4500 S ²⁻	2 ppm max

Note 1: ASTM D-3867 replaces discontinued ASTM D-992 per ASTM Standards and is authorized in ASME Table IWL-2525-1.

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.